

PACK MULE



RELIABLE PRODUCTS AND SERVICE

MAINTENANCE VEHICLE

MV 500 SERIES STANDARD FEATURES

- Dual Front Wheels
- Programmable Characteristics
- Sealed 300 Amp Controller
- Tamper-proof Speed Control
- Regenerative Braking
- Universal Hitch Plate
- On-board Diagnostics
- Maintenance Management System
- Contactor-less Drive System
- Sealed Direct Drive Transaxle
- · Sealed On-board Automatic Charger
- Battery Discharge Indicator
- LCD Hour Meter
- Heavy 14 Gauge Diamond Plate Steel Chassis
- Parking Brake



MV 550 Shown with optional equipment

Industrial environments demand a special kind of equipment. That's why Wesley International's electric vehicles are meticulously engineered for safety, reliability and low maintenance. From the dual front wheels to the sealed motor, Wesley's stock chasers offer increased stability and reduced down time. As a result, our Pack Mule stock chasers have been the choice of discerning buyers for years. They know that increased productivity and reduced maintenance costs deliver greater profit.

Our Pack Mule MV 500 series offers one and two-passenger vehicles that are perfect for maintenance personnel to quickly get around, with their tools and equipment. If our standard size doesn't fit your needs, we will custom build a vehicle that is just right for you. Our custom equipment is made with the same commitment to quality, safety and reliability.

Why buy a Pack Mule? Unique safety features, increased productivity, reduced maintenance and custom design...

Can you afford not to buy a Pack Mule?





PACK MULE



RELIABLE PRODUCTS AND SERVICE



MAINTENANCE VEHICLE

MV 500 SERIES OPTIONAL EQUIPMENT

- Perma-Key Switch
- Removable Battery System
- Battery Cart with Charger
- 245 Amp Hour Batteries
- Ergonomic Anti-Fatigue Mat
- Diagnostic Handset
- Small / Large Clipboard
- Headlight / Taillight
- Back-up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Rubber Deck Cover
- Non-marking Tires
- Dura Solid Tires
- Galvanized Frame
- Various Hitches

SPECIFICATIONS	MV 550	MV 520
Maximum Personnel	1	2
	DIMENSIONS	
Length	78 in. (198.1 cm)	
Width	29 in. (73.7 cm	36 in. (91.4 cm)
Height	50 in. (127 cm)	
Wheel Base	40 in. (101.6 cm)	
Ground Clearance	3 in. (7.6 cm)	
Deck Height	24 in. (61 cm)	
Deck Size	28.5 in. (72.4 cm) x 48 in. (121.9 cm)	
	CAPACITIES*	
Load Capacity	1000 lb. (453.6 kg)	1200 lb. (453.6 kg)
Towing Capacity	2000 lb. (907.2 kg)	
	WHEELS & TIRES	
Wheels	4	
Tires Pneumatic	4.80 x 8 LR B	
	ELECTRICAL	
Battery Type	220 amp hour	
System Voltage (Battery	24 volt (4-6 volt)	24 volt (4-6 volt)
Quantity)	36 volt (6-6 volt)	36 volt (6-6 volt) 48 volt (6-8 volt)
Sealed Motor (separatedly excited)	5 hp / 7.5 hp	5 hp / 7.5 hp/ 10 hp
Sealed Programmable Controller	300 amp	
Automatic Built-in Charger	16 amp, 3 stage charger	
Instrumentation	LED Battery Discharge, Hour Meter, Diagnostics	
Removable Key Switch	3 Position Safety Key Switch	
Horn	Push Button on Console	
	TRANSAXLE & TRANSMISSION	
Sealed Drive Axle	Heavy-duty Direct Drive Helical Gear	
Transmission Ratio	12.44:1	17.00:1
Programmable Maximum Speed	8 mph / 11 mph	8 mph / 11 mph /14 mph
STEERING, BRAKES & SUSPENSION		
Steering	3-Spoke Contour Wheel	
Service Brakes	Self-adjusting Wheel Drum Brakes	
Electronic Brakes	Programmable Electronic Regenerative Braking	

* Not to be combined. Can carry load or tow.

Specifications subject to change without notice. Wesley International electric vehicles are designed to conform with ANSI B56.8 and OSHA standards.

